

# **Temperature Data Logger EBI 12**

for quality control during pasteurization and sterilization

## **BLUE LINE**

The EBI 12 data logger is used for temperature measurement in canned food, jars, beverage cans and much more.

- High-quality stainless-steel housing
- Axial design
- M5 thread for attachment to the probe
- Application range from -55 °C to 150 °C
- High temperature accuracy of up to ±0.1 °C
- Version with two measuring channels Temperature sensor 3 mm, rigid

#### **Technical Data:**

Operating temperature	-55 °C +150 °C	
Measurement range	-55 °C +150 °C	
Accuracy	± 0.5 °C (-55 °C40 °C)	
	± 0.2 °C (-40 °C 0 °C)	
	± 0.1 °C (0 °C +150 °C)	
Resolution	0.01 °C	
Data memory	2x 13,920 measurements	
Sensor	PT1000, class A	
Measurement interval	1 s 24 hours	
Real-time data	No	
transmission		
Storage temperature	-20 °C +70 °C	
Measurement modes	<ul> <li>endless measurement</li> </ul>	
	<ul> <li>Measure upon starttime</li> </ul>	
	<ul> <li>Start immediately until end of</li> </ul>	
	memory	
	<ul> <li>Start- / Stop measurement</li> </ul>	
Battery	Lithium, 3.6 V,	
	User-replaceable	
Dimensions	(Ø x H) 48 mm x 24 mm	
Weight	App. 90 g	
Housing material	316 L stainless steel / PEEK	
Protection class	IP68	
Factory Calibration	-20 °C, 0 °C, +60 °C and +134 °C	
Certificate		



#### **Standards and Directives:**

- (EC) 1935/2004 Materials and articles which come into contact with food
- 2014/53/EU
   Radio Equipment Directive RED

Туре	Description	Part No.
EBI 12-T430	L 50 mm	1340-6614

Xylem Analytics Germany Sales GmbH & Co.KG, ebro -Peringerstr. 10 – D-85055 Ingolstadt, Germany Tel +49 841 954780 – Fax +49 841 95478-80

Website: www.ebro.com - E-Mail: ebro@xylem.com

ebro® is a registered trademark of Xylem Inc. or one of its subsidiaries. Technical changes reserved.

© 2014 Xylem Analytics Germany Sales GmbH & Co. KG.



### EBI 12-T430