





# **Temperature Data Logger EBI 12**

for food control during pasteurization, but also for monitoring, process and routine monitoring as well as temperature mapping...

## **BLUE LINE**

The EBI 12 data logger is used for temperature measurement in canned food, jars, beverage cans and much more.

- · High-quality stainless-steel housing
- Axial design
- M5 thread for attachment to the probe
- Application range from -40 °C to 140 °C
- High temperature accuracy of up to ±0.1 °C
- · Version with one measuring channels
- Temperature sensor 3 mm, rigid

#### **Technical Data:**

Operating temperature	-40 °C +140 °C	
Measurement range	-40 °C +140 °C	
Accuracy	± 0.2 °C (-40 °C 0 °C)	
	± 0.1 °C (0 °C +140 °C)	
Resolution	0.01 °C	
Data memory	27,840 measurements	
Sensor	PT1000, Class A	
Measurement interval	1 s 24 hours	
Real-time data	No	
transmission		
Storage temperature	-20 °C +70 °C	
Measurement modes	rement modes • endless measurement	
	Measure upon starttime	
	<ul> <li>Start immediately until end of</li> </ul>	
	memory	
	Start- / Stop measurement	
Battery Lithium, 3.6 V,		
·	User-replaceable	
Dimensions	(Ø x H) 48 mm x 24 mm	
Weight	app. 90 g	
Housing material	316 L stainless steel / PEEK	
Protection Class	IP68	
Factory Calibration	-20 °C, 0 °C, +60 °C and +134 °C	
Certificate		

### EBI 12-T237



#### Standards and Directives:

- (EC) 1935/2004
   Materials and articles which come into contact with food
- 2014/53/EU
   Radio Equipment Directive RED

Туре	Description	Part No.
	1 100	4040.000
EBI 12-T237	L 100 mm	1340-6637

